



PLASTIC Filters						
flow rates	filtration degrees	diameters	max. operating pressure			
up to 50 m³/h (220 US gpm)	3500 – 22 micron	³⁄4" – 3 "	10 bar (150 psi)			

Durable high quality Plastic filters for wide range of filtration applications



features:

- Interchangeable filter elements for wide range of flow rates, multiple filtration degrees and applications
- Excellent mechanical strength, corrosion resistance and models for chemical durability
- Low pressure loss
- Easy to install and maintain, no tools required for rinsing
- Available with exclusive features for semi-automatic cleaning
- Wide range of applications for the irrigation, municipal and industrial markets

amiad filtration solutions

Amiad Plastic Filters

General

With our various filter elements Amiad all purpose plastic filters are made for wide range of filtering applications and filtration degrees and are easy to install and maintain. They are constructed from high quality engineeringplastic materials for providing excellent mechanical strength, durability and in some of the models even corrosion and chemical resistance.

Amiad plastic filters need no tools for dismantling or for extracting the filter element from the filter housing for rinsing; also visually monitoring the status of the filter element without disrupting the water flow is easily done with Amiad's innovative clogging indicator connected to the filter's pressure check points.

Amiad plastic filters can be upgraded to semi-automatic operation by adding one of Amiad's exclusive Turboclean, Brushaway or Scanaway assemblies.

Filter Elements

Amiad supplies various filter elements for its plastic filters line in order to cover wide range of flow rates, filtration degrees and applications.

Screen Elements: (1)

These screen elements are constructed of molded plastic ribs that support a stainless steel weave-wire or weaved nylon screen for filtration degrees of 800 to 22 micron.

Perforated Stainless Steel Elements: (2)

Suitable for coarse filtration (straining) between 3,500 and 800 micron.

Disc Elements: (3)

The disc elements are made to provide high retention of organic substances and are constructed from plastic discs that are stacked onto a telescopic core.

The discs are grooved on both sides and intersected to form the filtration element when compressed on the telescopic core.

The effective filtration area is comprised of both the outside surface and the channels formed by the intersected grooves. Suspended organic particles adhere to the grooved surface adding depth to the filtration process. Cleaning the disc element is made simple by the unique design of the telescopic core which allows the discs to separate during the cleaning process while maintaining perfect sealing when the element is in the filter housing.



amiad filtration solutions

Filtration Degrees Available

The following table lists the various filter elements of Amiad's Plastic Filters line and the optional filtration degrees for each filter element. For ease of operation and maintenance the various filtration degrees are color coded, please consult your dealer for the most suitable filter element for your application's requirements.

Color	Brown	Green	Orange	Black	Yellow	Red	Purple	White	Brown	Blue	Green	Gray			
Micron	22	25	50	80	100	130	180	200	250	300	500	800	1500	2500	3500
Mesh	450	450	300	200	155	120	80	75	60	50	30	20	10	6	4
¾", 1"C	-														
1"S, 1½"C, 1½"S	-	*				■▲★			*			-			
2", 3"					▲★		*		*			•	•	•	٠

■ Nylon Screen ▲ Weave Wire Screen ★ Disc Element ● Perforated Screen



2"T Super







Head Loss Graphs

Dim. in mm (inch) *Approx. length required for maintenance

2″T









Dim. in mm (inch)

amiad filtration solutions



Technical Specifications

m i a d

а

Filter Type	2″ Т	2″ T-S	3" TL	3″ LT-S			
General Data	General Data						
Maximum flow rate*	25 m³/h (110 US gpm)	25 m³/h (110 US gpm)	50 m³/h (220 US gpm)	50 m³/h (220 US gpm)			
Inlet/Outlet diameter	2" (50 mm)	2" (50 mm)	3″ (80 mm)	3" (80 mm)			
Standard filtration degrees	3500, 2500, 1500, 800, 500, 300, 250, 200, 130, 100, 80, 50 micron						
Max. working pressure	10 bar (145 psi)						
Max. working temperature	60°C (140°F)						
Weight (empty)	Screen = 3.6 kg (7.9 lb) Discs = 4.4 kg (9.7 lb)	Screen = 4.2 kg (9.2 lb) Discs = 5.4 kg (11.9 lb)	Screen = 4.5 kg (9.9 lb) Discs = 5.7 kg (12.5 lb)	Screen = 9.2 kg (20.2 lb) Discs = 11 kg (24.2 lb)			

solutions

filtration





min 200 (8")



Dim. in mm (inch) *Approx. length required for maintenance

Engineering Data

а

Filter Type	2″ T	2″ T-S	З″ Т	3″ LT-S		
Filter Element Data						
Filter area	Screen = 465 cm ² (72 in ²) Discs = 790 cm ² (122 in ²)	Screen = 700 cm ² (108 in ²) Discs = 1185 cm ² (184 in ²)	Screen = 700 cm ² (108 in ²) Discs = 1185 cm ² (184 in ²)	Screen = 930 cm ² (145 in ²) Discs = 1580 cm ² (245 in ²)		
Filter Element type		Weave Wire Screen, Perfor	rated Screen, Disc Element			
t.						
Construction Materials*						
Filter bousing		Dolyamida + Class Fibors		Dolyacotal		

Filter housing	Polyamide + Glass Fibers	Polyacetal		
Filter Lid	Polyamide + Glass Fibers	Polyacetal		
Tightening nut	Polyamide + Glass Fibers	Polyacetal		
Clamp	N/A	St. St.		
Housing seal	NBR			
Screen	Construction = Polypropylene + Glass Fibers Mesh = St. St. Sv.	eals = NBR		
Discs	Construction = Polypropylene Grooved discs = polyethylene S	eals = NBR		

* Amiad offers a variety of construction materials. Consult us for specifications.



Technical Specifications

<u>m</u>i

а

Filter Type	1" Super	1½" Compact	1½" Super		
General Data					
Maximum flow rate*	7 m³/h (31 US gpm)	15 m³/h (66 US gpm)	15 m³/h (66 US gpm)		
Inlet/Outlet diameter	1" (25 mm)	1" 1½" (25 mm) (40 mm)			
Standard filtration degrees	800, 500, 300, 250, 200, 130, 100, 80, 50, 25, 22 micron				
Max. working pressure	10 bar (145 psi)				
Working temperature range	60°C (140°F)				
Weight (empty)	Screen = 0.52 kg (1.14 lb) Discs = 0.63 kg (1.38 lb)	Screen = 0.76 kg (1.67 lb) Discs = 0.86 kg (1.89 lb)	Screen = 1.0 kg (2.2 lb) Discs = 1.2 kg (2.64 lb)		

ad filtration solutions

* Consult Amiad for optimum flow depending on filtration degree \mathcal{E} water quality.



Filter Type	1" Super	1½" Compact	1½" Super				
Filter Element Data							
Filter area	Screen = 170 cm² (26.3 in²) Discs = 200 cm² (31 in²)	Screen = 170 cm² (26.3 in²) Discs = 200 cm² (31 in²)	Screen = 340 cm² (52.7 in²) Discs = 460 cm² (71.3 in²)				
Filter Element type	Nylon Screen, Weave Wire Screen, Disc Element						
	·						
Construction Materials*							
Filter housing	Polyacetal						
Filter Lid	Polyacetal						
Housing seal	NBR						
Screen	Construction = Polypropylene	Mesh = St. St. or Polyester Seals =	NBR				
Discs	Construction = Polypropylene	Grooved discs = Polyethylene Seals	= NBR				
	· · · · · · · · · · · · · · · · · · ·						

miad filtration solutions

а



Screen = 0.28 kg (0.61 lb)

* Consult amiad for optimum flow depending on filtration degree & water quality.

10 bar (140 psi)

60°C (140°F)

Screen = 0.30 kg (0.66 lb)

Max. working pressure**

Weight (empty)

Working temperature range

** Chemical resistant filters are rated to 8 bar.



HQ Screen filters - irrigation systems